# Station Automation Techniques & Recommendations

# Presented by Bob Wilson, N6TV <u>n6tv@arrl.net</u>





# **Presentation Overview**

- Why Automate?
- Transceivers
- Amplifiers
- Band Decoders
- Antenna Switches
- Bandpass Filters
- Tuners
- Summary of Recommendations
- Q & A





# Why Automate?

- Contesting is hard work
- You will get tired. You will get sleepy.
- Fatigue leads to *misteaks*
- Automation helps prevent *disastrous* mistakes
- Let the machines do what they do best
- You do the rest





# What should be automated?

- Computer Logging of:
  - Date, time, <u>frequency</u>, mode, callsign, exchange
- Most transmissions (CQ, Your Callsign)
  - CW, RTTY, Voice Keying
- Changing bands should automatically switch:
  - Antenna, Amplifier, Tuner
  - Bandpass filters / coax stubs
    (For Multi-Transmitter or SO2R)





# What should *not* be automated?

- CW copying
  - Do not rely on Code Readers
  - Do not blindly trust every cluster spot
- Voice Keying of Callsigns, Letter By Letter – "Oscar" "Hotel" "Two" "Bravo" "Alpha" "Delta"
- Exception: persons with disabilities
- How often to sign your call when running
- Where to call CQ





## Automating Band Changes Saves Time, and your Equipment

- Speed and Reliability is key
- Recommendation: Use hardware automation instead of software
  - Everything should switch automatically even when PC is OFF or rebooting
  - Not always possible for some transceivers or peripherals
- Transceivers provide "Band Data" or "Operating Frequency" data to Peripherals
- Peripherals track transceiver using "Band Data" or "Operating Frequency" inputs
  - Amplifiers and Tuners usually have RF Frequency Counters that will override incorrect input





## Transceiver Drives the Peripherals





Contest Academy

7

# **Band** Data

- Only provides transceiver's TX Band
  - Does not provide any VFO frequencies
- TX Band Data is ideal for:
  - Broadband solid-state amplifiers without tuners
    - KPA500, ACOM 500S, 600S, 700S, 1200S, PGXL, some SPE
  - Band decoders for antenna switches / BP filters
    - Top Ten, Bandmaster, ShackMaster SM-8, MD-12, Hamplus, BandPasser II, OM6BPF, Unified Micro BCD-14, EA4TX RemoteBox, Antenna Genius
- TX Band Data is *not* good enough for devices that need *exact* TX *frequency* 
  - Automatic tuners and amplifiers with auto tuners
    - Tuners: Kessler AT-AUTO, Elecraft KAT500, Tuner Genius
    - KPA1500, ACOM 2000A RCU, ACOM with 04AT/06AT tuner, most SPE
  - SteppIR controllers (FluidMotion, SDA100, SDA2000, OptimizIR)
  - Baby Loop controller





# **Band Data Encoding**

- Yaesu and Elecraft use 4-bit "BCD"
  - Binary Coded Decimal, "Band A" to "Band D"
- Icom uses 2-pin Band Voltage: "8V Ref", "Band"

Band		160m	80m	40m	30m	20m	17m	15m	12m	10m	6m	None
Frequency		1.8	3.5	7	10	14	18	21	24	28	<mark>50</mark>	NA
Icom Voltage		7.0v to 8.0v	6.0v to 6.5v	5.0v to 5.5v	0.1v to 1.2v	4.0v to 4.5v	3.0v to 3.5v	3.0v to 3.5v	2.0v to 2.5v	2.0v to 2.5v	1.2v to 2.0v	0v
	Band A	Н	L	Н	L	Н	L	Н	L	Н	L	L
Yaesu	Band B	L	н	Н	L	L	Н	Н	L	L	Н	L
	Band C	L	L	L	Н	Н	Н	Н	L	L	L	L
	Band D	L	L	L	L	L	L	L	Н	Н	Н	L

\* Icom outputs same voltage for 17m/15m and 12m/10m

- Flex band data output requires special cable
- Kenwood does not provide any band data output





### Yaesu Band Data Output Connectors

### – Yaesu FT-1000MP, FTdx5000, FTdx9000 Uncommon 262° <u>"Horseho</u>e" 8-pin DIN



### - FTdx10, FTdx1200 Uncommon 10-pin MINI DIN







### Yaesu Band Data Output Connectors

#### – Yaesu FTdx101D, FTdx101MP Standard DA-15F



- FT-710

Standard 8-pin MINI DIN – Set MENU TUN/LIN PORT SELECT to LINEAR

#### **TUNER/LINEAR**







# Elecraft Band Data Output

#### Elecraft K3 and K4

#### Standard 15-pin DE-15F Connector ("ACC")

Pin #	Description
1	FSK IN (see FSK Input)
2	AUXBUS IN/OUT (see KRC2 or XV- Series transverter instruction manual)
3	BAND1 OUT (see Band Outputs)
4	PTT IN (in parallel with MIC PTT)
5	Ground (RF isolated)
6	DIGOUT0 (see Transverter Control)
7	K3S ON signal (out) or TX INH (in) (see <b>Transverter Control</b> , <b>TX INH</b> )
8	POWER ON (see pg. 46)
9	BAND2 OUT (see Band Outputs)
10	KEYOUT-LP (10 mA keying output)
11	DIGOUT1 (see DIGOUT1)
12	Ground (RF isolated)
13	BAND0 OUT (see Band Outputs)
14	BAND3 OUT (see Band Outputs)
15	EXT ALC input (see External ALC, pg. 29)



Band	BAND3	BAND2	BAND1	BAND0
160 m	0	0	0	1
80 m	0	0	1	0
60 m	0	0	0	0
40 m	0	0	1	1
30 m	0	1	0	0
20 m	0	1	0	1
17 m	0	1	1	0
15 m	0	1	1	1
12 m	1	0	0	0
10 m	1	0	0	1
6 m	1	0	1	0





# ICOM "Band Voltage" Output

### - IC-7700, 7800, 7851, 7600, 7610, 7760

Standard 7-pin DIN:



#### IC-7300, IC-7410 Standard 13-pin DIN:



ACC	PIN No.	NAME
13-pin	1	8 V
	2	GND
(3 (9 (0 (1) (2) (5 6 7 8 (1 2 3 4)	3	SEND*1
Rear panel view	4	BDT
(1) brown (8) gray	· ·	
3 orange 10 black	5	BAND
(4) yellow (1) pink		
<ul><li>(5) green</li><li>(12) light</li><li>(6) blue</li><li>(6) blue</li></ul>	6	ALC
⑦ purple 13 light	7	NC
green	8	13.8 V
	9	TKEY
Color refers to the cable strands of the supplied cable.	10	FSKK
	11	MOD
	12	AF/IF (IF=12 kHz)*2
	13	SQL S



## Exact Frequency Output via RS-232



- COM is independent of Kenwood virtual USB port used by logger
- One device can "poll" radio for frequency via RS232 cable
- Yaesu FTdx3000, FTdx5000, FTdx9000 "CAT" DE-9M



- No USB, or FTdx3000 "CAT SELECT" = RS-232
- PC polls radio, peripherals "just listen" (Pin 2 wired, Pin 3 open)

**Contest Academy** 

• Custom RS-232 "Y-Cable" or "S-BOX" required for sharing



## Exact Frequency Output via RS-232

Yaesu FTdx10, FTdx101D, FTdx101MP
 DE-9M
 CAT
 Q @ Q @ Q SERIA OUT



- COM connector independent of USB
- One device can "poll" radio for frequency via RS232 cable
- Elecraft K3 or K3S DE-9F



- No independent USB connector (Elecraft K4 RS232 is independent)
- PC polls radio, peripherals "just listen" (Pin 2 wired, Pin 3 open)

**Contest Academy** 

• Custom RS-232 "Y-Cable" or "S-BOX" required



Exact Frequency Output via ICOM CI-V

 All ICOM rigs except IC-705 provide a legacy "REMOTE" (CI-V) connector

3.5mm MONO



- Two wire serial bus, 19200 baud max
- Important menu setting:
  Set USB CI-V Port to Unlink from [REMOTE]
  (Not available on older rigs like IC-7600, IC-7700)





# **Automatic Amplifiers**

- Usually Solid State and Broadband
- Often include built-in tuners
- Communicate with transceiver via Band Data, RS-232, ICOM CI-V, or Ethernet LAN
- Change bands automatically, no RF transmission required
- Usually have internal RF Frequency Counter as safety, in case RF input doesn't match band or frequency supplied from the transceiver

Contest Academy



# ACOM 2000A Amplifier

### – "New" RCU "CAT" connector: DE-15F (no Band Data pins)





Contest Academy



# ACOM Solid State Amplifiers – ACOM 500S, 600S, 700S, 1200S "CAT/AUX" connector: DE-15F 4-bit Band Data and RS-232

CAT/AUX interface	PIN NO.	PIN NAME	DESCRIPTION	SPECIFICATIONS	]	
	1	RxD	Received Data	TTL input	-	
	2	RxD	Received Data	RS232 input		
	3	TxD	Transmitted Data	RS232 output	_	
-0 <u>0</u> -	4	TxD	Transmitted Data	TTL output		
-00-	5	GND	Ground	0 Volt		
-000-	6	BAND voltage	Analogue input	0 to +8V		
-000-	7	Band data 0	Bit 0	TTL input	1	
Let-	8	Band data 1	Bit 1	TTL input	1	
	9	Band data 2	Bit 2	TTL input	1	
Rear panel	10	Band data 3	Bit 3	TTL input	1	
view	11	ON RMT	Remote Pwr On	+4.5 to + 15V / 3mA max	]	
	12	Debug mode	CPU only Pwr Input	+8 to + 15V / 0.4A	]	
	13	KEY-IN	Tx Request	Less than +12V / 6mA	1	
	14	KEY-OUT	Tx Ready	O.C. output, up to +50V / 20mA	]	
	15	GND	Ground	0 Volt		







# **Ameritron Solid State Amplifiers**

#### For ALS-500M, ALS-600, ALS-1300 series, use ARI-500 Interface and transceiver cables









Contest Academy



# Elecraft KPA500

"AUX" Connector: DE-15M for Band Data, K3/K4
 ICOM Band Voltage, but no ICOM CI-V support.
 RS232 "XCVR" Connector: DE-9M (RS232) for Kenwood



Signal Name	Pin	Direction	Notes
Band VRef (Icom)	1	In	Reference for Icom input – connect to 8V
AuxBus I/O	2	Out	K3 Only
Band1 In	3	In	BCD Band Input – Bit 1*
NC	4		
GND	5		
Band V (Icom)	6	In	Uses Icom standard band voltages
Alarm Out	7	Out	Drives low for fault input Not used by K3. Must not be connected to K3.
Power On/Off	8	In	Pulse low to turn KPA on or off – do not hold low!
Band2 In	9	In	BCD Band Input – Bit 2*
Кеу	10	In	Low enables amplification. Internally pulled up to +5V. Sources 1 mA when pulled to ground. Diode isolated from the PA KEY RCA jack.
Inhibit#	11	In	Low inhibits amplifier operation
GND	12		
Band0 In	13	In	BCD Band Input – Bit 0*
Band3 In	14	In	BCD Band Input – Bit 3*
ALC	15	Out	ALC output to transceiver





# Elecraft KPA1500

With built-in Antenna Tuner
 "AUX" Connector: DE-15M for K3/K4 Band Data, Elecraft AUXBUS, ICOM Band Voltage
 "XCVR Serial" Connector: 3.5mm TRS for Kenwood / Yaesu RS-232 or Icom CI-V



Signal Name	Pin	Direction	Notes
Band VRef (Icom)	1	In	Reference for Icom input – connect to 8V
AuxBus I/O	2	Out	K3 Only
Band1 In	3	In	BCD Band Input – Bit 1*
NC	4		
GND	5		
Band V (Icom)	6	In	Uses Icom standard band voltages
Alarm Out	7	Out	Drives low for fault input Not used by K3. Must not be connected to K3.
Power On/Off	8	In	Pulse low to turn KPA on or off – do not hold low!
Band2 In	9	In	BCD Band Input – Bit 2*
Кеу	10	In	Low enables amplification. Internally pulled up to +5V. Sources 1 mA when pulled to ground. Diode isolated from the PA KEY RCA jack.
Inhibit#	11	In	Low inhibits amplifier operation
GND	12		
Band0 In	13	In	BCD Band Input – Bit 0*
Band3 In	14	In	BCD Band Input – Bit 3*
ALC	15	Out	ALC output to transceiver







## FlexRadio Power Genius XL (PGXL)

DE-15F for Elecraft or Yaesu Band Data (x 2)
 DE-9M for RS-232 (x 2) or K4, Ethernet LAN port for Flex,
 3.5mm TS for ICOM CI-V (x 2)











### RF Kit RF2K-S

 USB Type A Connector Supports FTDI USB-to-Serial adapters or USB-to-CI-V (CT-17) interface cables, or LAN support. No Band Data input.









### SPE Expert 1K, 1.3K, 1.5K, 2.0K-FA

#### - DA-15F (x 2) for RS232, CI-V, and Band Data input







# Standalone Band Decoders

Connect Band Decoder input to transceiver

– Band Data, Icom Band Voltage, CI-V, or RS-232

- Connect Band Decoder output to Antenna Relay Box and/or Bandpass Filter Box
- Output is typically 13.8V "Source" or 0.0V "Sink", one line per band
- For triband antennas, Band Decoder can be programmed to select same output line for multiple bands





#### Hamation BandMaster III, IV, V, Shack Master SM-8, MD-12

- Decodes Band Data, RS-232, or ICOM CI-V
- Drives Antenna Relay box and/or BPF box



NCCC



## Hamation BandMaster III, IV, V, SM-8, MD-12

• All use the same DE-9M connector for Band Data, Icom Band Voltage, and RXD/TXD RS-232 DATA







## Elecraft KRC-2 Band Decoder

• Interior screw terminals for inputs and outputs









## HamPlus MBD-8G Band Decoder

- Decodes ICOM CI-V, Elecraft/Yaesu BCD, and Kenwood RS-232
- Drives HamPlus Antenna Relays, Bandpasser II Filter
- "SEND" In / Out jacks prevent antenna hot-switching during TX



**Contest Academy** 

30



### EA4TX RemoteBox

- Decodes Elecraft or Yaesu BCD, Icom Band Voltage (no CI-V)
- PTT input prevents hot-switching
- TX Inhibit option prevents transmission if two rigs are on same band



- Pin-4 Band Data C
- Pin-5 Band Data D

Pin-9: Band Voltage Input (ICOM)



# Top Ten Devices Band Decoder and Band Aide

- Yaesu/Elecraft Band Data
- No longer in production  $\mathfrak{S}$









#### Unified Microsystems BCD-14 + HSD-9

- Yaesu/Elecraft Band Data with "High Side Driver"
- "Some assembly required"











# Automatic Antenna Switches

- Controlled by one or two band decoders
- Switches to correct antenna automatically, when rig changes band
- Prevents two rigs from using the same TX antenna at the same time
- Uses low loss, high power relays





Ameritron RCS-8V and RCS-10 8- and 10-port Remote Coax Switches

- Replace the Ameritron manual switchbox with an automatic band decoder
- One +13.8V line in control cable selects one antenna port





35



#### Hamation EightPak 2x8 Antenna Switch

- Controlled by a Hamation Devices
- Prevents 2 radios from connecting to the same antenna at the same time







#### FlexRadio Antenna Genius 8x2 Switch

- Built-in Band Decoder (nice)
- DE-15F for Elecraft or Yaesu Band Data (x 2)
- Same Band Data pins as PGXL.
  LAN Port for Flex or PGXL
  New Dual PTT IN/OUT (RCA) prevent hot-switching





**Contest Academy** 



#### HamPlus AS-62 Antenna Switch

- 2 inputs, 6 Outputs
- Driven by HamPlus Band Decoder







# microHAM micro SIX and DOUBLE SIX, switches (10 port version also available)

- One +13.8V line in control cable selects antenna port
- Connect control cable to Band Decoder output









#### EA4TX AS2x8 Antenna Switch

### Connect control cable to RemoteBox output







# Automatic Bandpass Filters

- A must for operating SO2R, Multi-Op, or Field Day with more than one TX
- Attenuates nearby signals from adjacent bands
- 100 to 200W max. (typically)
- High Power BPFs are also available (4O3A), but much larger, much more expensive
- BPFs do not attenuate *in-band* harmonics
- Switch BPFs to correct band *automatically* to prevent filter damage, high SWR





#### Hamation AS-419 "BandPasser II"

• Built-in Band Decoder for Elecraft / Yaesu Band DATA









## DuneStar 600

 Requires Source or Sink Band Decoder to DE-9M connector (see manual)



DB9 Pin outs:

- (1) Brown 160M
- (2) Red 80M
- (3) Orange 40M
- (4) Yellow 20M
- (5) Green 15M
- (6) Blue 10M
- (7) Violet Ground (gray on older models)
- (8) White Not Used
- (9) Black +12V
  - Shell Shield





### OM Power OM6BPF

 Built-in Band Decoder (Elecraft, Yaesu, Icom Band Voltage)







**Contest Academy** 

NCC

44



# Automatic Antenna Tuners

- Once programmed for each segment, tuner remembers the tuning solution(s) for that frequency
- Tuner restores correct tuning solution, based on rig's frequency, well before you transmit
- Tuner can bypass itself automatically when SWR is low
- Tuner may remember multiple solutions per frequency to support multiple antennas





# Elecraft KAT500

- DE-15M and DE-15F passthrough for Elecraft AUX CABLES
- 3.5mm TRS "PC DATA" for Kenwood RS-232
- Safety feature: Opens amplifier keying line when tuning







## FlexRadio Tuner Genius XL (TGXL)

- Same connectors and pins as PGXL
- Recommendation: Use CAT or CI-V or LAN
- Safety feature: Dual PTT IN / OUT to amplifier (adds 6 ms delay)





**Contest Academy** 



## Kessler Engineering AT-AUTO

- Not to be confused with Palstar AT-AUTO
- The Kessler can track rig frequency by RS232 instead of RF





48



#### SteppIR Automatic Antenna Controller

NORM

- FluidMotion, SDA100, SDA2000, OptimizIR
- Tracks by RS-232 or CI-V set AutoTrack ON
- Custom SteppIR interface cable or S-BOX required
- "PTT" Relay Interrupt opens amp. keying line while antenna is tuning





SteppIR

Pattern = Normal

RETRACT POWER





WiMo Ultrabeam RCU-06 Antenna Controller

- Tracks by RS-232 or CI-V, Poll ON or OFF set by app.
- "PTT Tuning Relay" opens amp. keying line while tuning









"So how do I connect all this together?"







## **Interface Cables**

- Check DXE website or eBay
  - Many premade "Interface Cables" are listed
  - But some only provide a "Band Data" and "Keying" connection instead of RS-232 / Frequency.
- You can also try to build your own from the documentation and pinouts
- Things get more complicated when you need to split Band Data Outputs or a single RS-232 connector to multiple devices (PC, Amplifier, BP Filters, SteppIR Controller)





## Y-Cables for Band Data outputs

- Wiring Band Data Lines in parallel generally works OK, if voltages are compatible (PGXL needs pull-ups)
- Winford Engineering CDY15HDMFF:



N6TV Y-BOX:







## **Typical Y-BOX Block Diagram**







Sharing Transceiver RS-232 port requires special wiring

- Cannot wire two Pin 3s ("TXD") lines in parallel
- Simple DE-9 Y-cables will not work
- Connect only one TXD line to radio for polling
- Wire RXD lines (Pin 2) in parallel to all devices
- The N6TV S-BOX and S-BOX-USB
  - Connects rig to SteppIR controllers, ACOM, SPE, RF Kit, etc. using standard molded cables





Contest Academy

## **Typical S-BOX Block Diagram**









### Multiple Rigs, Antennas, but ONE Amp New microHAM TRIO

- Converts Band Data, CI-V, RS-232 to Common Format
- Switches Band Data, AMP Relay, ALC, TX Inhibit from 3 Radios







# **MicroHAM Trio Block Diagram**



Zeth Annual International Contest Academy

# **Key Recommendations**

- When possible, let the transceiver drive the devices, instead of PC ports or software
- Use Band Data when frequency is not needed
   BPFs, Antenna Switches, Broadband Amplifiers
- Use RS-232 or CI-V data when frequency is needed
  - Amps with tuners, SteppIR Controllers, automatic tuners
- Use off-the-shelf solutions if you're not comfortable wiring your own interconnection cables, in other words
- "If you don't know what you're doing, please don't do anything."



. . .



# References

- Product websites (Hamation, microHAM, Hamplus, etc.)
- <u>https://www.qrz.com/db/n6tv</u> Links to this and other presentations
- <u>https://bit.ly/Y-BOX</u> The "Y-BOX" by N6TV
- <u>https://bit.ly/S-BOX</u> The "Serial Box" by N6TV
- <u>n6tv@arrl.net</u>





# Questions?



